

# Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

**Supplier's name or trade mark:** Lumax

**Supplier's address:** Fjelland Handel, Sandvikveien 8, 4016 Stavanger, NO

**Model identifier:** TF2835-120P-5

## Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type (or other electric interface)	N/A		
Mains or non-mains:	MLS	Connected light source (CLS):	Yes
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Yes


## Product parameters

Parameter	Value	Parameter	Value
<b>General product parameters:</b>			
Energy consumption in on-mode (kWh/1000 h), rounded up to the nearest integer	9	Energy efficiency class	F
Useful luminous flux ( $\phi_{use}$ ), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	750 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	6 000
On-mode power ( $P_{on}$ ), expressed in W	8,5	Standby power ( $P_{sb}$ ), expressed in W and rounded to the second decimal	-
Networked standby power ( $P_{net}$ ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer, or the range of CRI-values that can be set	83
Outer dimensions without separate control gear, lighting control	Height	5 000	Spectral power distribution in the range 250 nm to 800 nm, at full-load
	Width	15	
	Depth	5	
			See image in last page

parts and non-lighting control parts, if any (millimetre)			
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-
		Chromaticity coordinates (x and y)	0,297 0,314
<b>Parameters for LED and OLED light sources:</b>			
R9 colour rendering index value	3	Survival factor	0,95
the lumen maintenance factor	0,97		
<b>Parameters for LED and OLED mains light sources:</b>			
displacement factor (cos $\phi_1$ )	0,82	Colour consistency in McAdam ellipses	4
Claims that an LED light source replaces a fluorescent light source without integrated ballast of a particular wattage.	-(b)	If yes then replacement claim (W)	-
Flicker metric (Pst LM)	0,8	Stroboscopic effect metric (SVM)	0,3

(a)-: not applicable;

(b)-: not applicable;



Model placed on the Union market from 15/09/2024.



**EPREL registration number:** 2069822

<https://eprel.ec.europa.eu/qr/2069822>

**Supplier:** T Fjelland & Co AS (Importer)

**Website:**

**Customer care service:**

**Name:** Fjelland Handel

**Website:**

**Email:** [firmapost@tfjelland.no](mailto:firmapost@tfjelland.no)

**Phone:** 51812300

**Address:**

Sandvikveien 8  
4016 Stavanger  
Norway